



# SINGLE-SPLIT WALL MOUNTED TYPE

Premium Series

# SRK-ZS-W



### Colour variation available

Users can choose their favorite colour from three choices.



Black & White (-WB)



Titanium (-WT)



Wireless remote control

SRK20ZS-W, SRK25ZS-W,  
SRK35ZS-W, SRK50ZS-W

Pure White(-W)



(P.17)



SRC20ZS-W, SRC25ZS-W2  
SRC35ZS-W2



SRC50ZS-W

## KEY FEATURES

- Elegant, timeless design, best suited for small to medium sized living spaces.
- Users can choose a color they like from three different choices.
- Low Global Warming Potential (GWP) and High energy efficiency by new refrigerant R32.
- Quiet Air Flow & Long Reach is achieved by jet technology.
- Allergen clear operation cleans air, using a control scheme owned only by Mitsubishi Heavy Industries Thermal Systems.
- Wireless interface control (optional) . **NEW**

## SPECIFICATIONS

| Indoor unit   |         |                         | SRK20ZS-W,-WB,-WT   | SRK25ZS-W,-WB,-WT     | SRK35ZS-W,-WB,-WT      | SRK50ZS-W,-WB,-WT       |
|---|---------|-------------------------|---|-----------------------|------------------------|-------------------------|
| Outdoor unit  |         |                         | SRC20ZS-W   | SRC25ZS-W2            | SRC35ZS-W2             | SRC50ZS-W               |
| Power source  |         |                         | 1 Phase, 220 - 240V, 50Hz   |                       |                        |                         |
| Nominal cooling capacity (Min~Max)                    |         | kW                      | 2.0(0.9~2.9)  | 2.5(0.9~3.1)          | 3.5(0.9~4.0)           | 5.0(1.3~5.5)            |
| Nominal heating capacity (Min~Max)                    |         | kW                      | 2.7(0.9~4.3)  | 3.2(0.9~4.5)          | 4.0(0.9~5.0)           | 5.8(1.3~6.6)            |
| Power consumption                                     |         | Cooling/Heating kW      | 0.44 / 0.59   | 0.62 / 0.74           | 0.89 / 0.94            | 1.35 / 1.56             |
| EER/COP   |         | Cooling/Heating         | 4.55 / 4.58   | 4.03 / 4.32           | 3.93 / 4.26            | 3.70 / 3.72             |
| Max. running current                                  |         | A                       | 9   | 9                     | 9                      | 14.5                    |
| Sound power level                                     | Indoor  | Cooling/Heating         | 48 / 50   | 50 / 53               | 54 / 56                | 59 / 60                 |
|   | Outdoor | Cooling/Heating         | 56 / 56   | 56 / 58               | 61 / 61                | 61 / 63                 |
| Sound pressure level                                  | Indoor  | Cooling (Hi/Me/Lo/Ulo)  | 34 / 25 / 22 / 19   | 36 / 28 / 23 / 19     | 40 / 30 / 26 / 19      | 46 / 36 / 29 / 22       |
|   | Outdoor | Heating (Hi/Me/Lo/Ulo)  | 36 / 29 / 23 / 19   | 39 / 30 / 24 / 19     | 41 / 36 / 25 / 19      | 46 / 37 / 31 / 24       |
| Air flow  | Indoor  | Cooling/Heating         | 45 / 45   | 46 / 46               | 50 / 48                | 51 / 52                 |
|   | Outdoor | Cooling (Hi/Me/Lo/Ulo)  | 9.3 / 7.0 / 5.9 / 5.0   | 9.9 / 8.0 / 5.9 / 5.0 | 11.3 / 8.7 / 7.0 / 5.0 | 12.1 / 9.9 / 7.4 / 5.9  |
| Exterior dimensions                                   | Indoor  | HeightxWidthxDepth      | 290 x 870 x 230   |                       |                        |                         |
|   | Outdoor | HeightxWidthxDepth      | 540 x 780(+62) x 290  |                       | 595 x 780(+62) x 290   |                         |
| Net weight  |         | Indoor / Outdoor        | 9.5 / 31.0  |                       | 9.5 / 34.5             |                         |
| Refrigerant   |         | Type/GWP                | R32 / 675   |                       |                        |                         |
|   |         | Charge                  | 0.62 / 0.419  |                       | 0.78 / 0.527           |                         |
| Refrigerant piping size                               |         | Liquid/Gas              | 6.35(1/4") / 9.52(3/8")   |                       |                        | 6.35(1/4") / 12.7(1/2") |
| Refrigerant line (one way) length [chargeless length] |         | ø mm                    | Max. 20 [15]  |                       |                        | Max. 25 [15]            |
| Vertical height differences                           |         | Outdoor is higher/lower | Max. 10 / Max. 10   |                       |                        | Max. 15 / Max. 15       |
| Outdoor operating temperature range                   |         | Cooling                 | -15~46  |                       |                        |                         |
|   |         | Heating                 | -15~24  |                       |                        |                         |
| Clean filter  |         |                         | Allergen Clear Filter x 1, Photocatalytic Washable Deodorising Filter x 1 |                       |                        |                         |

• The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27 CDB, 19 CWB, and outdoor temp. of 35 CDB. Heating: Indoor temp. of 20 CDB, and outdoor temp. of 7 CDB, 6 CWB.  
 • Sound level indicates the value in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.  
 • 'tonne(s) of CO<sub>2</sub> equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.